

Getac

Rugged Mobile Computing Solutions

T800

Fully Rugged Tablet



- 8.1" HD LumiBond® display for better viewing experience
- Getac proprietary SnapBack add-on featuring Smart card and contactless RFID reader Combo or 2nd expanded battery
- Choice of 1D/2D imager barcode reader, RS232, Micro SD or Ethernet
- LifeSupport™ battery swappable technology for uninterrupted battery life
- MIL-STD-810G and IP65 certified



Office Dock



SnapBack Add-on





Specification

Operating System	Windows® 8 Professional Windows® 7 Professional	Communication Interface	Optional 10/100/1000 base-T Ethernet (occupies expansion slot) Integrated 802.11ac WLAN; IEEE 802.11a/b/g/n compatible Bluetooth (v4.0 class 1) Optional SiRFstar1V™ GPS Optional Gobi™ mobile broadband
Mobile Computing Platform	Intel® Pentium® Processor N3530 2.16 GHz (2M Cache, up to 2.58 GHz)	Software	Getac Utility Getac Camera Getac V-GPS Barcode Utility Adobe Reader
VGA Controller	Intel® HD Graphics	Security Features	Optional SnapBack add-on: Smart card reader ⁱⁱⁱ with 13.56MHz contactless RFID reader ^{iv}
Display	8.1" TFT LCD HD (1280 x 800) 600 nits LumiBond® display with Getac QuadraClear® sunlight readable technology	Power	AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-Ion battery (7.4V, 4200) (up to 8 hours of battery life) ^v LifeSupport™ battery swappable technology
Storage & Memory	4GB DDR3L SSD 64GB / 128GB	Dimension (W x D x H) & Weight	227 x 151 x 24 mm 0.88kg ^{vi}
Keyboard	6 tablet buttons (Power, Home, Programmable, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)	Rugged Features	MIL-STD-810G certified and IP65 certified 6 feet drop resistant Optional ANSI/ISA 12.12.01 Vibration & drop resistant e Mark certified for vehicle usage
Pointing Device	Touchscreen - Capacitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer)	Environmental Specifications	Temperature ^{vii} : - Operating: -21°C to 50°C - Storage: -40°C to 71°C Humidity: - 95% RH, non-condensing
Expansion Slots	Choice of 1D/2D imager barcode reader, RS232, Micro SD or Ethernet ⁱ Optional SnapBack add-on: Smart card and contactless RFID reader combo ⁱⁱ Optional SnapBack add-on: 2nd expanded battery ⁱⁱ	Accessories	Carry bag Battery charger Battery (7.4V, 4200mAh) 2nd expanded battery (14.4V, 2100 mAh) AC adapter (65W, 100-240VAC) Vehicle adapter (90W, 11-16V DC and 22-32V DC) Capacitive stylus & tether Digitizer Shoulder strap (2-point) Hand-strap Wrist-strap Protection film Vehicle dock Office dock
I/O Interface	HD Webcam x 1 5MP rear camera with auto focus and LED x 1 USB (host 3.0) x 1 Headphone out/Mic-in Combo x 1 DC in Jack x 1 Micro HDMI x 1 Docking connector (24-pin) x 1 Optional SIM Card Slot x 1 Optional RF antenna pass-through for GPS, WWAN and WLAN		

Docking solution

	External VGA	Microphone	Audio Output	DC in Jack	USB	LAN	HDMI	RF antenna connector (WWAN, WLAN, GPS)
Vehicle Dock	--	--	--	1	2	1	--	3
Office Dock	1	1	1	1	4	1	1	--

ⁱ Barcode reader, Serial, Ethernet, and MicroSD port are mutually exclusive options.

ⁱⁱ All SnapBack add-ons are mutually exclusive options.

ⁱⁱⁱ 13.56MHz Contactless RFID and Smart Card reader (ISO 15693 and 14443 A/B compliant).

^{iv} Smartcard and Contactless RFID reader are mutually inclusive options.

^v Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions.

The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

^{vi} Weight varies from configurations and optional accessories.

^{vii} Tested by a national independent third party test lab following MIL-STD-810G.



Getac Technology Corporation

Mitac house, Nedge Hill, Telford,
Shropshire, TF3 3AH, U.K.
Tel: +44 1952 207 231
sales-getac-UK@getac.com
www.getac.co.uk

